

Edel Safegrass 20 CFL s1

Technical data sheet

A Product	
Product collection	Special
Product name	Edel Safegrass 20 CFL S1
Application	Garden lawns, roof gardens, patios, swimming pool surroundings, infrastructure, e.g.
B Production	
Producer	EDEL GRASS B.V. - Genemuiden - The Netherlands
Production process	Tufted, cut pile
C Pile	
Pile material	65% Polyethelene top yarn, 35% Polyporpelene thach
Yarn Dtex - total	7500 Dtex
Light fastness	> 7 on blue scale 1-8
Colour fastness	> 4 on grey scale 1-5
Quality	100% European product, free of heavy metals and toxics
D Product details	
Pile height in mm	20 ± 10%
Total height in mm	22 ± 10%
Pile weight in gr/m ²	740 ± 10%
Total weight in gr/m ²	2100 ± 10%
Gauge in inches	3/8
Stitch per 10 cm ¹	16 ± 10%
Stitches per m ²	16800 ± 10%
E Infill	
Stabilizing infill and gradation in mm	Silica-sand, minimum 80% round of shape 0.5 - 1.0
Recommendation ± in kg/m ²	5 For stabilisation
F Installation & Handling	
Installation method	Loose laid on bound or unbound sub-base
Available roll widths in m ¹	2 and 4 ± 2 cm
Roll length in m ¹	25 ±
G Warranty	
Warranty	8 years in Northern Europe 6 years in Southern Europe

The data above are subject to typing errors and modifications based on technical improvements or company-internal developments.

Version: 28-8-20 EB
CFL s1

All data are higher than the DIN-standards. All figures are average values and can vary slightly.