

# Edel Rise

PLAY THE WORLD

## A Product

<b>Product name</b>	Edel Rise
<b>Application</b>	Leisure@home Garden lawns, roof gardens, patios, swimming pool surroundings, infrastructure

## B Production

<b>Producer</b>	EDEL GRASS B.V. - Genemuiden - The Netherlands
<b>Production process</b>	tufted, cut pile

## C Pile

<b>Pile material</b>	PE monofilament straight & PP monofilament curled, combination of V-shape non directional, C-shape and oval shape texturized, environmental friendly, UV stabilized, free of lead and cadmium.
<b>Yarn Dtex</b>	21.000/24 dTex
<b>UV-stability</b>	DIN 53387 meets 6.000 hours W.O.M. test
<b>Light fastness</b>	> 7 on blue scale 1-8
<b>Colour fastness</b>	> 4 on gray scale 1-5

## D Backing

<b>Primary backing</b>	100% PP Thiobac <sup>®</sup> with fleece, black, UV-stabilised, total weight : 155 gr/m <sup>2</sup>
<b>Coating</b>	Carboxylated (SBR) latex, weight, 850 gr/m <sup>2</sup> with 4 mm perforation holes.
<b>Water permeability</b>	60 liter/min/m <sup>2</sup>

## E Product details

<b>Pile height</b>	40 mm	± 10%
<b>Total height</b>	42 mm	± 10%
<b>Pile weight</b>	1.400 gr/m <sup>2</sup>	± 10%
<b>Total weight</b>	2.405 gr/m <sup>2</sup>	± 10%
<b>Gauge</b>	5/8"	
<b>Stitches per m1</b>	115	± 10%
<b>Stitches per m2</b>	7.245	± 10%
<b>Filaments per m2</b>	347.760	± 10%

## F Installation

<b>Installation method</b>	loose laid on bound or unbound sub-base with or without shockpad or E-layer.
<b>Roll width</b>	4.00 m <sup>1</sup> (± 2 cm)
<b>Roll length</b>	25 m (± 20 cm)
<b>Joints/seams</b>	the seams in the turf are joined with a reinforcing tape glued to the back of the turf

The data above are subject to typing errors and modifications based on technical improvements or company-internal developments. All data are higher than the DIN-standards. All figures are average values and can vary slightly.

Page 1/1  
2-7-2024  
spec. Edel Rise (v1.1) (Eng.)

**Edel Grass BV**  
T. +31 (0)38 425 00 50  
E. info@edelgrass.com



edelgrass.com

**EDELGRASS**