

Edel Flashblade Enduro 60-10

PLAY THE WORLD

A Product

Product name	Edel Flashblade Enduro 60-10
Application	Rugby, Football, Soccer

B Production

Producer	EDEL GRASS B.V. - Genemuiden - The Netherlands
Production process	tufted, cut pile

C Pile

Pile material	Thiolon® PE monofilament yarn (XQ™ technology), propellor-shape, environment friendly, UV-stabilised.		
Yarn dtex	24.000/12 dTex		
Cross-section of tapes	Width :	1.25 mm	
	Thickness :	345 µm	
Colour	bicolour (field green and lime green)		
Line colour	white		
UV-stability	DIN 53387 meets 6.000 hours W.O.M. test		
Light fastness	> 7 on blue scale 1-8		
Colour fastness	> 4 on gray scale 1-5		

D Backing

Primary backing	polypropylene double layer, needle punched fleeced UV-stabilised, total weight : 246 gr/m ²		
Coating	Carboxylated (SBR) latex, weight, 988 gr/m ² with 4 mm perforation holes.		
Water permeability	> 1500 mm/h		

E Product details

Pile height	60 mm	± 5%
Total height	62 mm	
Pile weight	2.129 gr/m ²	± 10%
Total weight	3.363 gr/m ²	± 10%
Gauge	5/8"	
Stitches per m1	100	± 10%
Stitches per m2	6.300	± 10%
Filaments per m2	151.200	± 10%

F Installation

Installation method	loose laid on bound or unbound sub-base with or without shockpad or E-layer.
Roll width	4.00 m ¹ (± 2 cm)
Roll length	according to installation schedule
Joints/seams	the seams in the turf are joined with a reinforcing tape type 230 glued to the back of the turf
Line marking	tufted-in or to be laid in by installation

The data above are subject to typing errors and modifications based on technical improvements or company-internal developments. All data are higher than the DIN-standards. All figures are average values and can vary slightly.

Page 1/1
6-3-2026

spec. Edel Flashblade Enduro 60-10 (v1.1) (Eng.)

Edel Grass BV
T. +31 (0)38 425 00 50
E. info@edelgrass.com



 **edelgrass.com**

EDELGRASS